

## Signaling and remote control systems

# TOP GSM

### GSM remote control device

- Customizable SMS texts
- No supply mains signaling via SMS
- Output command via SMS or call



## GENERAL SPECIFICATIONS

- Operating voltage 12Vdc/230Vac
- Quad-band GSM module
- N°9 telephone numbers for inputs status communication
- N°9 telephone numbers for power failure communication (only with buffer battery)
- ECHO function for checking SIM expiration and residual credit
- Buffer battery (SC100.19/P1/xxx)
- GSM/GPRS antenna with magnetic base and 3m cable
- Connection terminal board
- External thermoplastic box
- Cable glands
- Protection degree IP65
- Operating temperature -5/+40°C

## INPUTS / OUTPUTS

- N°4 completely programmable low voltage inputs
- N°2 inputs for temperature probe
- N°2 outputs max 5A NC-COM-NO (pure contact)
- N°2 outputs max 5A COM-NO (pure contact)

CODE	TYPE	INPUTS	OUTPUTS	POWER SUPPLY	DIMENSIONS mm			WEIGHT Kg	BOX
					A-H	L-W	P-D		
SC100.19/1	TOP GSM 4/1	4	1	230Vac	140	80	0,6	01	03
SC100.19/4	TOP GSM 4/4	4	4	230Vac	140	80	0,6	01	03

## OPTIONALS

CODE	TYPE
OP100.09/2	Wired lithium battery 3,7Vdc 600mAh