

TOP ALARM

Visual and acoustic alarm indicator with siren shut-off button and buffer battery



ADVANTAGES

- Supply mains absence signaling
- Adjustable alarm delay
- Siren shut-off



GENERAL SPECIFICATIONS

- Operating voltage 12Vdc/230Vac
- Deactivable supply mains absence alarm signaling
- Siren shut-off button
- Alarm delay trimmer OFF/1÷18min
- Visual Led indicator
- Acoustic indicator
- Buffer battery 12Vdc 1,3Ah with charger (SS101.01)
- Connection terminal board
- External thermoplastic box
- Cable glands
- Protection degree IP55
- Operating temperature -5/+40°C

INPUTS / OUTPUTS

- Very low voltage input for external command
- Alarm output max 5A NC-COM-NO (pure contact)

CODE	TYPE	INDICATOR		AUTONOMY	POWER SUPPLY	DIMENSIONS mm			WEIGHT Kg	BOX
		VISUAL	ACOUSTIC			A-H	L-W	P-D		
SS101.00	TOP ALARM VA 12/230	Led	90dB	-	12Vdc/230Vac	180	140	110	0,7	02
SS101.01	TOP ALARM VAB 230	Led	90dB	24h	230Vac	180	140	110	1,3	02

SPARE PARTS

CODE	TYPE
SD101.230	Single-phase TOP ALARM electronic board