

## Fire-fighting control panels

# BASIC ALARM EN

Visual and acoustic alarm indicator for fire-fighting units (UNI EN-12845)

### GENERAL SPECIFICATIONS

- Operating voltage 230Vac
- Siren shut-off button
- Lamps test button
- Green supply mains Led light
- TYPE A red alarm Led light
- TYPE B yellow alarm Led light
- Acoustic indicator
- Buffer battery 12Vdc 1,3Ah with charger
- Connection terminal board
- External thermoplastic box
- Cable glands
- Protection degree IP55
- Operating temperature -5/+40°C



### INPUTS / OUTPUTS

- N. 3 very low voltage NC input for type A alarms
- N. 10 very low voltage NC input for type B alarms
- Alarm output max 5A NC-COM-NO for type A signaling
- Alarm output max 5A NC-COM-NO for type B signaling

### ADVANTAGES

- Possibility to connect up to 3 EN fire-fighting panels
- Supply mains absence signaling
- Siren shut-off
- Lamps test

CODE	TYPE	INDICATOR		AUTONOMY	POWER SUPPLY	DIMENSIONS mm			WEIGHT Kg	BOX
		VISUAL	ACOUSTIC			A-H	L-W	P-D		
SS900.00	BASIC ALARM EN VAB 230	Led	90dB	24h	230Vac	285	245	140	2,3	03

### SPARE PARTS

CODE	TYPE
SD900.230	Single-phase BASIC ALARM EN electronic board