

Fire-fighting control panels

TOP ALARM EN

Visual and acoustic alarm indicator with RS-485 connection for fire-fighting units (UNI EN-12845)

GENERAL SPECIFICATIONS

- Operating voltage 230/400Vac
- Siren shut-off button
- Lamps test button
- Led lights for signaling alarms and anomalies for each panel
- Signaling maintained even in the absence of main power
- Possibility to connect up to 2 alarm panels
- Acoustic indicator
- Buffer battery 12Vdc 1,3Ah with charger
- Connection terminal board
- External thermoplastic box
- Cable glands
- Protection degree IP55
- Operating temperature -5/+40°C



INPUTS / OUTPUT

- RS-485 port for connection to different units
- Cumulative alarm output max 5A NC-COM-NO

ADVANTAGES

- Possibility to connect up to 3 EN fire-fighting panels to each alarm module
- Possibility to connect up to 2 alarm modules
- Simplified connection thanks to RS-485 serial port
- Supply mains absence signaling
- Siren shut-off
- Lamps test

CODE	TYPE	INDICATOR		AUTONOMY	POWER SUPPLY	DIMENSIONS mm			WEIGHT Kg	BOX
		VISUAL	ACOUSTIC			A-H	L-W	P-D		
SS901.00	TOP ALARM EN VAB 230	Led	90dB	24h	230Vac	200	260	100	2	-