

Electromechanical control panels

EVO 1 RANGE 0,5÷25HP

Direct starting electromechanical control panel 1 motor



GENERAL SPECIFICATIONS

- Operating voltage 230Vac $\pm 10\%$ 50/60Hz (SA621.xx)
- Operating voltage 400Vac $\pm 10\%$ 50/60Hz (SA631.xx)
- General disconnecting switch with door lock
- Selector switch for automatic -0- manual operation (stable)
- Mains supply Led light
- Running Led light
- Overload Led light
- Auxiliary circuit protection fuse
- Transformer for auxiliary circuit
- Motor protection fuse
- Contactor
- Thermal relay (internal reset)
- Connection terminal board
- External thermoplastic box
- Cable glands
- Protection degree IP55
- Operating temperature -5/+40°C

PROTECTIONS

- Maximum current protection with alarm

INPUTS / OUTPUTS

- N°2 very low voltage input for pressure switch or float switches (minimum/maximum level)

SINGLE-PHASE 230Vac ±10% 50/60Hz

CODE	TYPE	POWER		OPERATING CURRENT [A]	DIMENSIONS mm			WEIGHT Kg	BOX
		kW	Hp		A-H	L-W	P-D		
SA621.00L	EVO 1 230 0,5	0,37	0,5	2,5÷4	345	285	165	5,4	04
SA621.01L	EVO 1 230 0,75	0,55	0,75	4÷6,5	345	285	165	5,4	04
SA621.02L	EVO 1 230 1	0,75	1	6,3÷10	345	285	165	5,4	04
SA621.03L	EVO 1 230 1,5	1,1	1,5	6,3÷10	345	285	165	5,4	04
SA621.04L	EVO 1 230 2	1,5	2	9÷14	345	285	165	5,4	04
SA621.05L	EVO 1 230 3	2,2	3	13÷18	345	285	165	5,4	04

THREE-PHASE 400Vac ±10% 50/60Hz

CODE	TYPE	POWER		OPERATING CURRENT [A]	DIMENSIONS mm			WEIGHT Kg	BOX
		kW	Hp		A-H	L-W	P-D		
SA631.00L	EVO 1 400 0,5	0,37	0,5	1,1÷1,6	345	285	165	5,4	04
SA631.01/02L	EVO 1 400 1	0,55÷0,75	0,75÷1	1,6÷2,5	345	285	165	5,4	04
SA631.03L	EVO 1 400 1,5	1,1	1,5	2,5÷4	345	285	165	5,4	04
SA631.04L	EVO 1 400 2	1,5	2	4÷6,5	345	285	165	5,4	04
SA631.06/07L	EVO 1 400 4	2,2÷3	3÷4	6,3÷10	345	285	165	5,4	04
SA631.09L	EVO 1 400 5,5	4	5,5	9÷14	345	285	165	5,4	04
SA631.10L	EVO 1 400 7,5	5,5	7,5	13÷18	345	285	165	5,4	04
SA631.11L	EVO 1 400 10	7,5	10	17÷23	345	285	165	5,4	04
SA631.12L	EVO 1 400 12,5	9,2	12,5	20÷25	345	285	165	5,4	04
SA631.13/14L	EVO 1 400 17,5	11÷13	15÷17,5	24÷32	345	285	165	5,5	04
SA631.15L	EVO 1 400 20	15	20	32÷38	380	300	150	6,5	05
SA631.16L	EVO 1 400 25	18,5	25	35÷50	380	300	210	8,1	06





OPTIONALS

CODE	TYPE
OP100.02/0	Automatic -0- manual selector switch (from stable to unstable)
OP100.07/3	Wired start-stop button
OP100.03/xx/1	Wired capacitor (xx)µF with electronic circuit breaker 230Vac see page 116
OP100.04/4	Wired lack, sequence and asymmetry of phases relay
OP100.04/5	Wired lack, sequence and asymmetry of phases relay, minimum and maximum voltage
OP100.05	Wired single-phase surge arrester type 2
OP100.05/1	Wired three-phase surge arrester type 2
OP100.15/024	Wired hour counter 24Vac 48x48
OP100.16/1	Wired analog daily timer 72x72 without reserve
OP100.16/2	Timer analogico giornaliero 72x72 con riserva cablato
OP100.19/4	Wired module GSM 4 inputs/4 outputs
OP100.09/2	Wired lithium battery 3,7Vdc 600mAh
OP331.230	Wired LEVEL 230Vac control relay
OP100.01	3 level probes kit
OP100.17/024	Wired interface 24Vac relay complete with socket
OP100.17/024/ST	Wired interface 24Vac relay (thermal trip)
OP100.17/024/CE	Wired interface 24Vac relay (external command)
OP210.01	Wired very low voltage input for motor klaxon
OP200.00/1	Alarm output 24Vac and pure contact
OP100.13/1	Wired siren shut-off button
OP100.13/1/24	Wired siren 24Vac/dc
OP100.13/2/24L	Wired flashing Led lamp 24Vac
SS100.01	Visual and acoustic alarm indicator (BASIC ALARM VA 024) see page 20
SS101.01	Visual and acoustic alarm indicator with buffer battery (TOP ALARM VAB 230) see page 19
OP00.10	Couple of brackets for collar (reference BOX 03-04)

STANDARD
CONTROL PANEL

CONTROL PANEL WITH OPTIONAL:
OP331.230

CONTROL PANEL WITH OPTIONAL:
OP200.00/1



KEY COMPONENTS

- Float switch for clean water**
- Float switch for sewage**
- Level probes**

The addition of some optionals can imply changes on the size of the control panel. For further details please contact our technical/commercial department.