TOP ALARM EN

Visual and acoustic alarm indicator with RS-485 connection for fire-fighting units (UNI EN-12845)

GENERAL SPECIFICATIONS

- Operating voltage 230/400Vac
- Siren shut-off button
- Lamps test button
- Led lights for signaling alarms and anomalies for each panel
- Signaling mantained even in the absence of main power
- Possibility to connect up to 2 alarm panels
- Acoustic indicator
- Buffer battery 12Vdc 1,3Ah with charger
- Connection terminal board
- External thermoplastic box
- Cable glands
- Protection degree IP55
- Operating temperature -5/+40°C



INPUTS / OUTPUT

- RS-485 port for connection to different units
- Cumulative alarm output max 5A NC-COM-NO

ADVANTAGES

- Possibility to connect up to 3 EN fire-fighting panels to each alarm module
- Possibility to connect up to 2 alarm modules
- Simplified connection thanks to RS-485 serial port
- Supply mains absence signaling
- Siren shut-off
- Lamps test

CODE	TYPE	INDICATOR VISUAL	INDICATOR ACOUSTIC	AUTONOMY	POWER SUPPLY	DIMENSIONS mm A-H	DIMENSIONS mm L-W	DIMENSIONS mm P-D	WEIGHT Kg	BOX
SS901.00	TOP ALARM EN VAB 230	Led	90dB	24h	230Vac	200	260	100	2	-